

DTD

Temperature Controller

Features:


- 4 Control Modes: ON/OFF, PID, Manual and PID Programmable Control
- PID Parameter Auto-Tuning
- Input Signals: Sensor or Analog Signals
- 9 Alarm Output Modes
- Strong Alarm Functions: Standby Alarm Output, Alarm Output Inversion, Holding Alarm Output and Displaying Alarm Peak Value






Dimensions

DTD 4848



DTD 4896



Ordering Information

DTD 1 2 3 4 5 0

Series name	DTD: Delta D series temperature controller	
1 2 3 4 Panel size (W x H)	4848 : 1/16 DIN W48 x H48 mm	4896 : 1/8 DIN W48 x H96 mm
5	R: Relay output SPST (250VAC, 5A) V: Voltage pulse output 14V +10% ~ -20% (Max. 40mA)	
Optional	0 : None	

Specifications

Power input	AC100 ~ 240V 50/60Hz	
Input power range	85% ~ 110%, rated voltage	
Power consumption	6VA Max.	
Display	7-segment LED; PV in red, SV in green	
Input temperature sensor	Thermocouple: K, J, T, E, N, R, S, B, L, U, TxK	Platinum resistance: Pt100, JPt100
Analog input	Current: 0 ~ 20mA, 4 ~ 20mA,	Voltage: 0 ~ 5V · 0 ~ 10V · 0 ~ 70mV
Display scale	For temperature input: K2, J2, T2, Pt100-2 and JPt100 can display to 0.1 degree; others display in 1degree as a unit. °	
Control method	PID, PID programmable control, On/Off, manual output	
Control output type	Relay output: AC 250V, 5A, SPST Voltage pulse output: DC 14V, Max. output current 40mA	
Sampling cycle	0.4 second (including analog input signal and sensor input signal)	
Vibration resistance	10 ~ 55Hz 10m/s ² 3 axes 10mins	
Shock resistance	Max. 300m/s ² 3 axes 6 directions, 3 times each	
Ambient temperature	0°C ~ 50°C	
Storage temperature	-20°C ~ +65°C	
Operation altitude	Less than 2,000m	
Ambient humidity	35% ~ 85% RH (non-condensing)	



ASIA

Delta Electronics, Inc.
Taoyuan
31-1, Xingbang Road, Guishan Industrial Zone,
Taoyuan County 33370, Taiwan, R.O.C.
TEL: 886-3-362-6301 / FAX: 886-3-362-7267

Delta Electronics (Jiang Su) Ltd.

Wujiang Plant3
1688 Jiangxing East Road,
Wujiang Economy Development Zone,
Wujiang City, Jiang Su Province,
People's Republic of China (Post code: 215200)
TEL: 86-512-6340-3008 / FAX: 86-512-6340-7290

Delta Electronics (Japan), Inc.

Tokyo Office
Delta Shibadaimon Building, 2-1-14 Shibadaimon,
Minato-Ku, Tokyo, 105-0012, Japan
TEL: 81-3-5733-1111 / FAX: 81-3-5733-1211

Delta Electronics (Korea), Inc.

Donghwa B/D 3F, 235-6, Nonhyun-dong,
Kangnam-gu, Seoul 135-010, Korea
TEL: 82-2-515-5303/5 / FAX: 82-2-515-5302

Delta Electronics (Singapore) Pte. Ltd.

8 Kaki Bukit Road 2, #04-18 Ruby Warehouse Complex,
Singapore 417841
TEL: 65-747-5155 / FAX: 65-744-9228

Delta Energy Systems (India) Pvt. Ltd.

Plot No. 27 & 31, Sector-34, EHTP,
Gurgaon-122001 Haryana, India
TEL: 91-124-4169040 / FAX: 91-124-4036045

AMERICA

Delta Products Corporation (USA)

Raleigh Office
P.O. Box 12173, 5101 Davis Drive,
Research Triangle Park, NC 27709, U.S.A.
TEL: 1-919-767-3813 / FAX: 1-919-767-3969

EUROPE

Deltronics (The Netherlands) B.V.

Eindhoven Office
De Witbogt 15, 5652 AG Eindhoven, The Netherlands
TEL: 31-40-2592850 / FAX: 31-40-2592851

*The content in the catalog may be revised without prior notice to clients.