



NOTES.

1. Match Motor Flange: $\phi 70$
2. Output shaft have keyway, without keyway is optional.
3. Bushing is supplied to input bore $\phi 10$, $\phi 14$, $\phi 16$ or $\phi 22$
4. $\phi C = \phi 19$ or $\phi 24$

Ration Application	15~100
Power Application	400W ~ 1.5KW

MODEL	段數 (Stage)	減速比 (Ratio)	背隙 (Arcmin)	匹配馬達出軸直徑&長度
PS090-A0205C1430	雙段	20	5	14 & 30
PS090-A0305C1430	雙段	30	5	14 & 30
PS090-A0205C1935	雙段	20	5	19 & 35
PS090-A0305C1935	雙段	30	5	19 & 35

DELTA 台達電子工業股份有限公司
DELTA ELECTRONICS, INC.

Drawn: _____ Design: _____

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.

THIRD ANGLE PROJECTION
Description: **Planetary Gearhead Servo Box**

DIMENSIONAL TOLERANCES () HOLES: ± 0.05 ANGLES: $\pm 0.5^\circ$
 <30 : ± 0.25 DECIMALS UP-100 : ± 0.2 250-300 : ± 0.4 UP-600 : ± 1.5
 >30-100 : ± 0.35 X : ± 0.3 100-150 : ± 0.25 300-350 : ± 0.45 600-900 : ± 2.4
 >100-300 : ± 0.5 X,X : ± 0.2 150-200 : ± 0.3 350-400 : ± 0.5 900-OVER : ± 3.1
 ABOVE 300 : ± 0.6 X,XX : ± 0.1 200-250 : ± 0.35

A3
SIZE

Part No. _____ REV. _____
 X0

SCALE _____ UNIT mm USED ON **Planetary Gearhead**
 SHEET OF _____ ISSUE DATE: _____