



- NOTES.**
1. Match Motor Flange: $\phi 70$
 2. Output shaft have keyway, without keyway is optional.
 3. Bushing is supplied to input bore $\phi 10$, $\phi 14$, $\phi 16$ or $\phi 22$
 4. $\phi C = \phi 19$ or $\phi 24$

MODEL	段數 (Stage)	減速比 (Ratio)	背隙 (Arcmin)	匹配馬達出軸直徑&長度
PS090-C0053C1430	單段	5	3	14 & 30
PS090-C0103C1430	單段	10	3	14 & 30
PS090-C0053C1935	單段	5	3	19 & 35
PS090-C0103C1935	單段	10	3	19 & 35

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.	Drawn:	Design:
	Description: Planetary Gearhead Servo Box	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.	THIRD ANGLE PROJECTION	Part No.
DIMENSIONAL TOLERANCES () : ±0.25 DECIMALS UP-100 : ±0.2 250-300 : ±0.4 UP-600 : ±1.5 >30-100 : ±0.35 X : ±0.3 100-150 : ±0.25 300-350 : ±0.45 600-900 : ±2.4 >100-300 : ±0.5 X,X : ±0.2 150-200 : ±0.3 350-400 : ±0.5 900-OVER : ±3.1 ABOVE 300 : ±0.6 X,XX : ±0.1 200-250 : ±0.35	A3 SIZE	REV.
SCALE: _____ UNIT: mm USED ON: Planetary Gearhead	SHEET OF _____ ISSUE DATE: _____	X0

Ration Application	3,4,5,6,7,8,9,10
Power Application	400W ~ 1.5KW