



**NOTES.**

1. Match Motor Flange:  $\phi 110$
2. Output shaft have keyway, without keyway is optional.
3. Bushing is supplied to input bore  $\phi 19$ ,  $\phi 22$  or  $\phi 24$
4.  $\phi C = \phi 28$  or  $\phi 32$

MODEL	段數 (Stage)	減速比 (Ratio)	背隙 (Arcmin)	匹配馬達出軸直徑&長度
PS120-A0205E2255	雙段	20	5	22 & 55
PS120-A0305E2255	雙段	30	5	22 & 55
PS120-A0205E2455	雙段	20	5	24 & 55
PS120-A0305E2455	雙段	30	5	24 & 55

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.		Drawn:	Design:
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.		Description: <b>Planetary Gearhead Servo Box</b>	
DIMENSIONAL TOLERANCES ( ) ( ) ( ) ( ) ( ) ( ) <30 : ±0.25 DECIMALS UP-100 : ±0.2 250-300 : ±0.4 UP-600 : ±1.5 >30-100 : ±0.35 X : ±0.3 100-150 : ±0.25 300-350 : ±0.45 600-900 : ±2.4 >100-300 : ±0.5 X.X : ±0.2 150-200 : ±0.3 350-400 : ±0.5 900-OVER : ±3.1 ABOVE 300 : ±0.6 X.XX : ±0.1 200-250 : ±0.35		Part No. _____ REV. _____ X0	
SCALE	UNIT	mm	USED ON
A3		Planetary Gearhead	
SIZE		SHEET OF ISSUE DATE:	

Ration Application	15~100
Power Application	750W ~ 3.75KW