



NOTES.

1. Match Motor Flange: $\phi 110$
2. Output shaft have keyway, without keyway is optional.
3. Bushing is supplied to input bore $\phi 19, \phi 22$ or $\phi 24$
4. $\phi C = \phi 28$ or $\phi 32$

Ration Application	3,4,5,6,7,8,9,10
Power Application	750W ~ 3.75KW

MODEL	段數 (Stage)	減速比 (Ratio)	背隙 (Arcmin)	匹配馬達出軸直徑&長度
PS120-C0053E2255	單段	5	3	22 & 55
PS120-C0103E2255	單段	10	3	22 & 55
PS120-C0053E2455	單段	5	3	24 & 55
PS120-C0103E2455	單段	10	3	24 & 55

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.		Drawn:	Design:
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.		Description: Planetary Gearhead Servo Box	
DIMENSIONAL TOLERANCES () : ±0.25 DECIMALS UP-100 : ±0.2 250-300 : ±0.4 UP-600 : ±1.5 >30-100 : ±0.35 X : ±0.3 100-150 : ±0.25 300-350 : ±0.45 600-900 : ±2.4 >100-300 : ±0.5 X.X : ±0.2 150-200 : ±0.3 350-400 : ±0.5 900-OVER : ±3.1 ABOVE 300 : ±0.6 X.XX : ±0.1 200-250 : ±0.35		A3 SIZE	Part No.
SCALE	UNIT		mm
Planetary Gearhead		SHEET OF ISSUE DATE:	
		REV. X0	