



NOTES.

1. Match Motor Flange: $\phi 114.3$
2. Output shaft have keyway, without keyway is optional.
3. Bushing is supplied to input bore $\phi 22, \phi 24, \phi 28$ or $\phi 32$
4. $\phi C = \phi 35$ or $\phi 38$

Ration Application	3,4,5,6,7,8,9,10
Power Application	1KW ~ 7.5KW

MODEL	段數 (Stage)	減速比 (Ratio)	背隙 (Arcmin)	匹配馬達出軸直徑&長度
PS142-C0053F3579	單段	5	3	35 & 79
PS142-C0103F3579	單段	10	3	35 & 79

台達電子工業股份有限公司 DELTA ELECTRONICS, INC.		Drawn:	Design:
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUS OR DEVICES WITHOUT PERMISSION.		Description: Planetary Gearhead Servo Box	
DIMENSIONAL TOLERANCES () HOLES: ± 0.05 ANGLES: $\pm 0.5^\circ$ <30 : ± 0.25 DECIMALS UP-100 : ± 0.2 250-300 : ± 0.4 UP-600 : ± 1.5 >30-100 : ± 0.35 X : ± 0.3 100-150 : ± 0.25 300-350 : ± 0.45 600-900 : ± 2.4 >100-300 : ± 0.5 X,X : ± 0.2 150-200 : ± 0.3 350-400 : ± 0.5 900-OVER : ± 3.1 ABOVE 300 : ± 0.6 X,XX : ± 0.1 200-250 : ± 0.35		A3 SIZE	Part No.
SCALE	UNIT mm		USED ON Planetary Gearhead
SHEET		OF	ISSUE DATE: